



Espacenet


Bibliographic data: JP 6000168 (A)

METHOD AND DEVICE FOR MEASURING ELECTRIC IMPEDANCE DISTRIBUTION

Publication date: 1994-01-11
Inventor(s): YOSHIOKA SENJI; OZAWA KAZUMASA; YOKOTA NORIKATSU; SUZUKI HIROAKI +
Applicant(s): HITACHI LTD +
Classification: - international: A61B5/05; (IPC1-7): A61B5/05
- European:
Application number: JP19920162816 19920622
Priority number(s): JP19920162816 19920622

Abstract of JP 6000168 (A)

PURPOSE: To enhance the accuracy for a reconstitution image by collecting at a high speed potential distribution data used for an electric impedance CT method. **CONSTITUTION:** In the periphery of a measuring object 5, many electrodes 4a-4h are arranged, and from a multi-signal simultaneous supply device 1, electric signals of each different frequency are applied simultaneously to each electrode. A multi-signal simultaneous measuring device 2 measures simultaneously the peripheral potential of the measuring object 5, and a tomographic image reconstituting device 3 executes a frequency analysis of the measured potential, and derives a measured value of a potential distribution in the periphery of the measuring object 5 to each frequency. Subsequently, a tomographic image of an electric impedance distribution for showing an internal state of the measuring object 5 is reconstituted by a numerical calculation.



Last updated: 12.10.2011
Worldwide Database 5.7.23.2. 93p